

PS120304B

PN: PSAD-12CB21X-CK01B
EAN: 6422956008154

Specifications

Input	
Nominal Voltage AC	AC 100 ~ 240 V
Frequency Range	50Hz ~ 60 Hz
Output	
Nominal Voltage	DC 12V
Total Output Current	3A
Total Output Channel	4 channels
Fuse Rating	PTC1.1A/CH
Ripple & Noise	<=120mv
Efficiency	>=80%
Battery compatibility	12V 7Ah / 12V 9Ah
	151 x 65 x 93 mm
Environment	
Storage Temperature	-30°C ~ 70°C
Operating Temperature	-10°C ~ 45°C
Physical	
Product dimensions	264 x 206 x 90 mm
Product weight	1.89 kg
Retail Pack Dimensions	271 x 214 x 96 mm
Retail Pack Weight	2.04kg



Individual PTC Fuse



Back-up battery function



Metal box

- Universal AC input
- Regulated 12Vdc low voltage output (adjustable from 12-15V via PSU trimmer)
- Individually PTC fused terminals
- LED indicator per output
- With back-up battery function
- Short circuit protection, high voltage protection, over current protection

Logistics

Carton Box Size (LxWxH)	560 x 398 x 231 mm
Pieces in the Carton Box	8
Net & Gross weight / CTN	N.W.: 15.2 kg / G.W.: 17.3 kg



Certificates

RoHS 2011/65/EU CE